



GOODMAN-BENTLEY
(SPEC/OPS) DESIGN & SECURITY
COMPANY

TECHNICAL SPECIFICATION
W.O.L.V.E.S 2

TRANSMITTER

FREQUENCY 2.414 – 2.468 GHz Four Channel
OUTPUT POWER 2 Mw
BANDWIDTH 18 MHz
MODULATION MODE FM
BATTERY Rechargeable Lithium Battery
providing 5 hours
AUDIO Built in microphone
STANDBY TIME 30 Days
BATTERY CAPACITY 500 Mah
CHARGE TIME 2 Hours
OPERATING TEMPERATURE -10 TO +50
CHANNELS Four Channels on Transmitter

1. 2.414
2. 2.432
3. 2.450
4. 2.468

CAMERA CMOS Colour (628 X 582 Pixels)
VIEWING ANGLE 62 Degrees
RESOLUTION 380 TV Lines
MINIMUM ILLUMINATION 1.5 Lux / F1.5
SIZE 41mm x 23mm x 23mm
WEIGHT 40 Grammes
RANGE 200 – 400 Metres

RECEIVER

RECEIVING FREQUENCY ISM 2.400 – 2483 4Channels
INTERMEDIATE FREQUENCY 480 MHz
ANTENNAES AVAILABLE 50 ohm/ 8db / 14 db gain selectable for range
POWER SUPPLY +12V
DIMENSIONS 78 X 92 X 23 mm
WEIGHT 200 Grammes

